

TrafficGuard® LANECOLOR 12

ODORLESS SOLUTION FOR COLORFUL DEMARCTION



TECHNICAL DATA SHEET FOR PROFESSIONAL CONTRACT USE ONLY

DESCRIPTION

LANECOLOR 12 is the next generation, odor free and environmentally friendly lane demarcation system transforming the installations of bus and bike lanes, symbols, legends, crosswalks and various surface applied directional safety markings. **LANECOLOR 12** maintains UV stability and weather resistance in the harshest of conditions while providing durability under heavy vehicular traffic. It may be mixed and applied by hand and allows for a full return to service within 40 minutes.

FEATURES

- **ODORLESS and ENVIRONMENTALLY FRIENDLY**
- User friendly with a simple 1:2 mix ratio by volume
- No special installation equipment required
- Convenient pot life with 15 minutes of working time
- Accepts mixed or broadcast aggregates of various sizes for high friction performance

BENEFITS

- Safe installations for cities and neighborhoods without odor concerns
- Quick Return to service time of under 40 minutes
- Versatile performance properties that provide exterior toughness and surface movement unaffected by heavy twisting tires or seasonal freeze/ thaw cycles.
- Preserves roads with 100% solids chemistry resisting shrinkage and surface cracking
- Color stability for long lasting and aesthetically pleasing markings
- Excellent bond strength and retention of aggregate to maintain friction

USES

- Bus and Bike Lanes
- Pedestrian walks
- Crosswalks
- Toll plazas
- Sports stadiums
- Parking Structures
- Universities / Campuses
- Industrial markings

SURFACE PREPARATION

The surface must be free of curing compounds/sealers, oil, grease, and all debris. Existing markings shall be removed when specified by governing agency. When placed over existing markings, the surface shall be cleaned by means of water blasting, sand blasting, shot blasting or other manufacturer accepted procedures. Any existing markings with flaking or delamination areas shall be removed prior to the installation of **LANECOLOR 12**. Application shall not take place under precipitation of any type such as rain, sleet or snow. First time users should always consult with ChemCo Systems prior to installation. Recommended ambient temperature window for outdoor installations is 40° F - 120° F.

PACKAGING & COLORS

- Side A: 1 Part; Side B: 2 Part
- Standard package sizes of 5-gallon pails, 50-gallon drums, 250-gallon totes.
- Colors: Bus Lane Red and Bike Lane Green, White, Yellow, Safety Yellow (Customs colors available upon request)

STORAGE AND SHELF LIFE

12 months in factory delivered unopened containers. Avoid extreme heat, cold, and moisture. Maintain at a proper storage temperature of 60°F - 80°F (16°C -27°C).

TECHNICAL DATA

PHYSICAL PROPERTIES	TEST METHOD	VALUE
Solids Content, Percent Solids		100%
Mix Ratio, By Volume		1A:2B
Elongation	ASTM D638	>7%
Hardness, Shore D	ASTM 2240	79
Pot Life (Working Time)		13 – 15 minutes
Return to Service	> 60°	< 35 minute
Adhesion to Concrete	ASTM 4541	> 800 psi
Adhesion to Asphalt	ASTM 4541	> 400 psi
Tensile Strength	ASTM D638	6937 psi avg.





Limited Warranty: Please read all information in the General Guidelines, Technical Data Sheets, Guide Specifications and Safety Data Sheets (SDS) before applying material. These products are for professional use only and to be applied by professionals who have prior experience and training with the use and application of our materials, and who are fully aware of all Federal, State and local rules, regulations, and code requirements for storage, transportation, handling, installation, and application. Published technical data and instructions are subject to change without notice. Contact your local representative or visit our website for current technical data, SDS, instructions, and project specific recommendations. We warrant our products to be free of manufacturing defects and that they will meet our current published physical properties within the shelf life of products.

Our sole responsibility shall be to replace that portion of the product which proves to be defective. There are no other warranties of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. We will not be liable for damages of any sort, including remote or consequential or punitive damages resulting from any claimed breach of any warranty whether expressed or implied. We will also not be responsible for use of this product in a manner to infringe on any patent held by others. No warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, adhesion, peeling, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and/or physical movement of the substrate or structural defects are also excluded from the limited warranty. We reserve the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator. Your sole and exclusive remedy against us shall be limited to the paid cost of the materials sufficient to replace any affected areas where product failure has occurred. The cost of replacement materials shall, in no event, exceed the value of the original purchase price of the products, subject to equitable reductions for time of use.

Disclaimer: We are not a professional contractor, engineering company, consultant, or applicator. We are a manufacturer and we are not a designer/engineer/applicator of record and do not provide advice. We do not specifically review, endorse, or approve of any proposals, owner's specifications, project specifications, or other arrangements. All guidelines, recommendations, statements, and technical data contained herein are based on information and tests conducted in controlled conditions and do not represent applicable for all environments and we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. As a user, you will remain responsibility to satisfy yourself, based on your own information and test, to determine suitability of the product for your own intended use, application and job situation and you assume all risk and liability resulting from use of the products. We do not suggest or guarantee that any hazard listed herein are the only ones which may exist. We are not liable to any user or any third person for any injury, loss or damage directly or indirectly resulting from use of, or inability to use, the product. No recommendations or statements, whether verbal or in writing, shall be binding upon us except as provided herein, or as provided in writing and signed by an authorized corporate officer. Technical and application information is provided for the purpose of establishing a general profile of the material and proper application procedures. Not responsible for typographical errors.

© 2026 ChemCo Systems. All rights reserved. Revision 20260115.AG