MATERIAL SAFETY DATA SHEET

ChemCo Systems, Inc., 2800 Bay Road, Redwood City, CA 94063 Prepared by Dept. of Safety, Phone: 650/261-3790

24 Hour Emergency Phone: 800.424.9300 (202-483-7616) CHEMTREC

1. PRODUCT NAME:

CCS™ Binder, Bridge Deck, Part A Chemical Family: Epoxy resin mixture.

2. HAZARDOUS INGREDIENTS

NAME	CAS No.	TLV	STEL	PEL	CONTENT
Epoxy resin	25068-38-6	none	none	none	75-85%
Epoxy resin (CGE)	2210-79-9	none	none	none	15-25%
Category Reference Petroleum Distillate	68477-31-6	none	none	none	<3%

reference section 7, Health Hazard Data for LD (50)

3. PHYSICAL DATA:

Boiling Point:	>200 C	Water/Oil Distribution Coefficient:	N/D		
Percent Volatile:	Negligible	Solubility in Water:	Minimal		
Freezing Point	N/D	Specific Gravity:	1.1		
Vapor Pressure @ 20C:	N/D	pH:	N/D		
Vapor Density	Heavier than air	Evaporation Rate:	N/D		
Odor Threshold	N/D	Odor	Mild		
Appearance	Amber liquid				

N/D = Not Determined

4. FIRE AND EXPLOSION HAZARD DATA:

HMIS Flammability Rating:	1 - (Slight Hazard)		
Flash Point:	> 250 F (PMCC)		
Auto Ignition Temperature:	N/D		
Limits of Flammability:	LEL: N/D	UEL: N/D	
EXTINGUISHING MEDIA:			

CARBON DIOXIDE, FOAM, DRY CHEMICAL AND WATER FOG SPECIAL FIRE & UNUSUAL HAZARDS: At high temperatures vapors can cause pressure build-up in sealed containers. Use water to cool containers exposed to fire. Self-contained respirator equipment and full protective clothing required when smoke or fumes are generated. Electrical grounding not recommended.

5. REACTIVITY DATA:

HMIS Reactivity Rating:	1 - (Slight Hazard)
STABILITY: This product requires	another component to read

at room temperature. Excessive heat and fume generation can occur if improperly handled. Not sensitive to mechanical impact.

INCOMPATIBILITY: Strong acids, strong bases. Amines and mercaptains may initiate possible hazardous polymerization.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and dioxide, aldehydes, various hydrocarbons from incomplete combustion.

HAZARDOUS POLYMERIZATION: May occur is product is not handled per instructions.

6. ENVIRONMENTAL AND DISPOSAL INFORMATION:

ACTION TO TAKE FOR SPILLS AND LEAKS: Wear appropriate protective gear. Contain leak/spill. Salvage. Clean up residue with absorbent material.

WASTE DISPOSAL METHOD: Handle disposal of waste material in manner which complies with local, state, province, and federal regulations. Landfill if solidified or incinerate at agency approved waste-disposal facility.

7. HEALTH HAZARD DATA:

HMIS Hoalth Pating

ПІМІЭ	nealth Rating. 2 - (Moderate nazard)			
Primar	y Route Of Entry: Dermal			
Effects of Overexposure:				
Skin	Prolonged or repeated exposure may cause skin irritation			
Contact:	and redness. Skin sensitization or allergic reaction may			
	occur in some individuals.			
Eyes:	Contact may cause irritation, redness, tearing and blurred vision.			
Inhalation	No known health information on inhalation of vapors. At higher temperatures fumes may be irritating and cause sensitization.			
Ingestion:	Low oral toxicity.			
	LD (50) CAS 25068-38-6 11.4 g/kg (rat)			
	LD (50) CAS 2210-79-9 4 g/kg (rat)			
Chronic:	Prolonged or repeated overexposure may cause			
sensitization or other allergic reactions. CGE is reported				
to be mutagenic in vitro.				

8: FIRST AID:

	6. FIRST AID.
Inhalation	Remove victim from exposure. If difficulty with breathing; administer oxygen and seek immediate medical assistance.
Eyes:	Flush with water, lifting upper and lower lids occasionally for 15 minutes. Seek medical attention.
Skin:	Wash with soap and water; get medical attention if irritation persists.
Ingestion:	Do not give liquid if victim is unconscious or very drowsy; otherwise give no more than two glasses of water or milk and induce vomiting with two tablespoons of Syrup of Ipecac or by touching finger to back of victim's throat. Keep victim's head below hips while vomiting. Seek medical attention.

9. SPECIAL PROTECTION INFORMATION:

HMIS Perso	nal Protection Rating: C (Safety Glasses, Gloves, Apron)			
Ventilation:	Ventilation is recommended. Air movement must be			
	designed to insure turnover at all locations in work area to prevent build-up of heavy vapors.			
Personal	Use eye protection. Selection of specific items such as			
Protection:	gloves, boots and apron will depend on the operation.			

10. ADDITIONAL INFORMATION:

DOT Proper Shi	pping Name:	Epoxy resin mix	ture		
DOT Hazard Cla	ass or Division:	Not regulated			
Identification Nu	mber:	N/A			
Packing Group:		N/A			
Labels Required	:	N/A			
WHMIS Classific	cation:	Class D, Div. 2,	Sub. B.		
WHMIS Labeling	g:	Stylized T			
Storage		rs tightly sealed. S	tore in c	dry ar	nd cool
Conditions:	areas. Avoid fr	eezing conditions.			
Shelf life:		Indefinite.			
Special	Storage re	commendations:	Store	at	room
Instructions:	temperature.	Do not allow to free	eze.		

The information given herein is given in good faith. No warranty, expressed or implied, is made regarding the accuracy of these data or the results obtained from the use thereof. All materials may present unknown health hazards and must be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Consult ChemCo Systems Inc. for further information.

MSD128A 04/14