

MATERIAL SAFETY DATA SHEET

ChemCo Systems, Inc., 2800 Bay Road, Redwood City, CA 94063

Prepared by Dept. of Safety, Phone: 650/261-3790

24 Hour Emergency Phone: 800.424.9300 (202-483-7616) CHEMTREC

1. PRODUCT NAME:
KEMKO® 175 Clear SEAL, Part B
Chemical Family: Polyamines

2. HAZARDOUS INGREDIENTS

NAME	CAS No.	TLV	STEL	PEL	CONTENT
Dimer of TOFA/TETA Reaction Product	68082-29-1	none	none	none	40-45%
Triethylenetetramine	112-24-3	none	none	none	3%

reference section 7, Health Hazard Data for LD (50)

3. PHYSICAL DATA:

Boiling Point:	N/D	Water/Oil Distribution Coefficient:	N/D
Percent Volatile:	<1.0%	Solubility in Water:	Slight
Freezing Point	N/D	Specific Gravity:	1.3
Vapor Pressure @ 20C:	N/D	pH:	basic
Vapor Density	N/D	Evaporation Rate:	N/D
Odor Threshold	N/D	Odor	Ammoniacal
Appearance	Black paste		

N/D = Not Determined

4. FIRE AND EXPLOSION HAZARD DATA:

HMIS Flammability Rating:	1 - (Slight Hazard)
Flash Point:	>100 C (TCC)
Auto Ignition Temperature:	N/D
Limits of Flammability:	LEL: Unknown UEL: Unknown
EXTINGUISHING MEDIA:	CARBON DIOXIDE, FOAM, DRY CHEMICAL & WATER FOG.
SPECIAL FIRE & UNUSUAL HAZARDS:	Self-contained respirator equipment and full protective clothing are required when smoke and fumes are generated. Electrical grounding is not recommended.

5. REACTIVITY DATA:

HMIS Reactivity Rating:	1 - (Slight hazard)
STABILITY:	Stable. This product must be mixed with another component to react. Not sensitive to mechanical impact.
INCOMPATIBILITY:	Strong oxidizing agents, acids, epoxy resins, isocyanates and organic peroxides may result in violent explosive reactions.
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon monoxide and dioxide, nitrogen oxides, aldehydes and various hydrocarbons from incomplete combustion.
HAZARDOUS POLYMERIZATION:	Will not occur unless product is mixed with epoxy resins, isocyanates or urethane prepolymers..

6. ENVIRONMENTAL AND DISPOSAL INFORMATION:

ACTION TO TAKE FOR SPILLS AND LEAKS:	Ventilate area. Wear appropriate protective gear. Contain leak/spill. Clean up residue with absorbent material. Wash down area with water and diluted acetic acid. Prevent washings from entering waterways.
WASTE DISPOSAL METHOD:	Handle disposal of waste material in manner which complies with local, state, province, and federal regulations. Landfill if solidified or incinerate at agency approved waste-disposal facility.

7. HEALTH HAZARD DATA:

HMIS Health Rating:	2- (Moderate Hazard)
Primary Route Of Entry:	Dermal, Ingestion
Effects of Overexposure:	
Inhalation	Due to low vapor pressure of this product, fumes will be minimal below 90F. At higher temperatures, fumes will be irritating.
Eyes:	Contact can cause severe burns and irreversible damage, irritation, redness, tearing or blurred vision.
Skin Contact:	Short single exposure may cause moderate irritation to mild burn. Prolonged or repeated exposure may cause a severe burn. May result in an allergic reaction or sensitization response in some individuals. Dermal LD(50) (rabbit), 2g/kg (estimate)
Ingestion	Intake can cause gastrointestinal irritation, nausea, vomiting, diarrhea, headache and drowsiness. Can result in burns of mouth esophagus and stomach. Moderately toxic. LD (50) (rat), > 2g/kg
Chronic:	None known.

8: FIRST AID:

Eyes:	Flush eyes with water and/or 1% boric acid, lifting upper and lower lids occasionally for 30 minutes. Seek prompt medical attention.
Skin:	Wash with soap and water for at least 15 minutes. Remove contaminated clothing and wash before re-use. Destroy contaminated leather. Seek medical attention if irritation persists.
Ingestion	Do not induce vomiting. Give large quantities of water or vinegar diluted with water. Get immediate medical attention. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person.
Inhalation	Remove victim from exposure. If difficulty with breathing; administer oxygen and seek immediate medical assistance.

9. SPECIAL PROTECTION INFORMATION:

HMIS Personal Protection Rating:	C (Safety Glasses, Gloves, Apron)
Ventilation	Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid the build up of heavy vapors.
Personal Protection	Use eye protection and gloves. . Selection of specific items such as gloves, boots and apron will depend on the operation. Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for listed hazard. Confined spaces, rooms or tanks are areas where concern for TLV's is especially important. Reference OSHA Regulation CFR 29 1910.134 for recommended respiratory protection.

10. ADDITIONAL INFORMATION:

DOT Proper Shipping Name:	Polyamide mixture
DOT Hazard Class or Division:	Not Regulated
Identification Number:	N/A
Packing group:	N/A
Labels Required:	N/A
WHMIS Classification:	Class D, Div. 2
WHMIS Labeling:	Stylized T.
Shelf life:	18 months, minimum.
Special Instructions:	Storage recommendations: Store at room temperature. Do not allow to freeze.
Title III, Section 313 Reporting:	None

The information given herein is given in good faith. No warranty, expressed or implied, is made regarding the accuracy of these data or the results obtained from the use thereof. All materials may present unknown health hazards and must be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Consult ChemCo Systems Inc. for further information.

MSD175B 04/14