

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Kemko 136 Strip SEAL, Part B
SYNONYMS: 136B
PRODUCT CODES: 136B

MANUFACTURER: ChemCo Systems Inc.
ADDRESS: 2800 Bay Road
Redwood City, Ca. 94063
PHONE: 650 261-3790

EMERGENCY PHONE:
Chemtrec: Domestic: 800 424-9300
International: +1 703 527-3887

RECOMMENDED USE: Polyurethane, For further information refer to the Product Data Sheet

SECTION 2: HAZARDS IDENTIFICATION

GHS Hazard:



ROUTES OF ENTRY: EYE: YES SKIN: YES INGESTION: YES INHALATION: YES

SIGNAL WORD: Warning!

PHYSICAL HAZARDS: Not Classified

HEALTH HAZARDS: (ACUTE AND CHRONIC)

EYES: No Data
SKIN: No Data
INGESTION: No Data
INHALATION: Acute toxicity inhalation:Cat.4

CARCINOGEN: Carc. Cat.1

ENVIRONMENTAL HAZARDS:

Not Classified

HAZARD STATEMENTS: H302 – Harmful if swallowed.
H351 - Suspected of causing cancer.

PRECAUTIONARY STATEMENTS:

P261 – Avoid breathing mist/vapors/spray.
P262 - Do not get in eyes, on skin, or on clothing
P264 - Wash...thoroughly after handling with soap and water
P301+P312: IF SWALLOWED: Immediately call a POISON CENTER/doctor if you feel unwell.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338 - IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 – If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 – If eye irritation persists: Get medical advice/attention.
P362 – Take off contaminated clothing and wash before reuse.
P501 -Dispose of contents/container to an approved waste disposal plant.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Persons with preexisting skin or respiratory disorders may have their conditions aggravated by over exposure to this material.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS	CAS #:	CAL-OSHA PEL TWA (8hours)	ACGIH TLV TWA (8 hours)	Other Limits RECOMMENDED	% BY WEIGHT
4,4'-methylenebis[N-sec-butylaniline]	5285-60-9	No Data Available	No Data Available		<50
Treated fumed silica	67762-90-7	No Data Available	No Data Available		<9
Talc	14807-96-6	No Data Available	No Data Available		<4
Quartz(fine fraction)	14808-60-7	No Data Available	No Data Available		<0.5
Chlorite-group minerals	1318-59-8	No Data Available	No Data Available		<0.1
Alkyl phthalates (c6-c13)	None	No Data Available	No Data Available	5mg/m3 Exxon	<50

				Mobile	
Carbon black	1333-86-4	No Data Available	No Data Available		<0.1

SECTION 4: FIRST AID MEASURES

- EYES:** Immediately flush eyes with water for a minimum of 15 minutes while holding eyes open. Remove contact lenses if present and easy to do. If redness, burning, blurred vision, or swelling persists, consult a physician.
- SKIN:** Remove contaminated clothing and product. Immediately wash affected area with soap and water. Do not apply greases or ointments. If skin irritation persists, consult a physician.
- INGESTION:** Rinse mouth immediately. Give small amounts of water, only if person is conscious. Only induce vomiting at the instruction of medical personnel. consult a physician
- INHALATION:** Remove patient to fresh air. Give oxygen or artificial respiration if needed. If patient continues to experience difficulty breathing, consult a physician.

SECTION 5: FIRE-FIGHTING MEASURES

- SUITABLE EXTINGUISHING MEDIA:** Extinguish with foam, carbon dioxide, dry powder, or water fog.
- SPECIAL FIRE FIGHTING PROCEDURES:** Use standard fire-fighting procedures and consider the hazards of other involved materials. In case of a fire and / or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.
- HAZARDOUS DECOMPOSITION PRODUCTS:** Hazardous decomposition products may occur when material polymerizes at temperatures above 500 °F (260 °C). Irritating and toxic gases/fumes may be released during a fire. Do not allow run-off from fire-fighting to enter drains or water courses.
- FLASH POINT:** >200 °F / 93 °C
- METHOD USED:** (PMCC)

SECTION 6: ACCIDENTAL RELEASE MEASURES

- PERSONAL PROTECTION:** Keep unnecessary personnel away. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate personal protective equipment. Do not touch containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Local authorities should be advised if significant spillage cannot be contained.
- ACCIDENTAL RELEASE MEASURES:** In case of spill, clean up using absorbent material such as earth or sand. Small quantities can be wiped up with cloth, place cloth in leak proof container and dispose of properly.
- WASTE DISPOSAL:** Observe Federal, State and local regulations covering chemical waste spills.

SECTION 7: HANDLING AND STORAGE

- PERSONAL PROTECTION:** Use personal protective equipment to ensure product does not contact eyes or skin when handling materials.
- HANDLING AND STORAGE:** Store in cool dry place out of direct sun rays. Keep from freezing. Recommend storage temperatures range: between 40° and 95 °F (4° - 35 °C)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE MEASURE: Wear appropriate personal protective equipment.

EYE PROTECTION: Wear appropriate safety glasses with side shields, goggles or full face shield. When working on an overhead application a full face shield is recommended.

HAND PROTECTION: Wear chemical-resistant gloves such as: Nitrile, neoprene, butyl.

SKIN AND BODY PROTECTION: Wear long sleeve shirts/long pants and other clothing as required to minimize contact.

RESPIRATORY PROTECTION: Do not breathe gas/fumes/vapor/ or spray. The use of a respirator is not required during general use of this product provided adequate ventilation. If grinding or cutting cured product the use of an approved respirator is recommended.

WORK HYGIENIC PRACTICES: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

ENGINEERING CONTROLS: When using indoors, good ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Ready access to running water is required. Provide eyewash station.

EXPOSURE LIMITS

Component	OSHA (PEL)	ACGIH (TLV)	NIOSH (Pocket Guide)
4,4'-methylenebis[N-sec-butylaniline] 5285-60-9	No Data	No Data	No Data
Talc 14807-96-6	TWA 20mppcf	No Data	TWA 2mg/m3 (resp)
Quartz (fine fraction) 14808-60-7	No Data	No Data	TWA 0.05 mg/m3
Chlorite-group minerals 1318-59-8	No Data	No Data	No Data
Treated fumed silica 67762-90-7	No Data Available	TWA 3mg/m3	No Data Available
Carbon black 1333-86-4	No Data Available	No Data Available	No Data Available

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Black

ODOR: Ammonia

PHYSICAL STATE: Paste

pH AS SUPPLIED: N/D

BOILING POINT: >300 C

MELTING POINT: N/D

FREEZING POINT: N/D

VAPOR PRESSURE: <0.1mm Hg 20C

VAPOR DENSITY (AIR = 1): N/D

SPECIFIC GRAVITY (H2O = 1): 1.0

EVAPORATION RATE: Negligible

SOLUBILITY IN WATER: Negligible

PERCENT SOLIDS BY WEIGHT: N/D

PERCENT VOLATILE: N/D

VOLATILE ORGANIC COMPOUNDS (VOC): ND

MOLECULAR WEIGHT: ND

VISCOSITY: 7000 poise

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID (STABILITY): Exposure to excessive heat and open flame

INCOMPATIBILITY (MATERIAL TO AVOID): Strong acids, peroxides and other oxidizing agents.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Normal combustion forms carbon dioxide, carbon monoxide, oxides o carbon and other organic compounds,

HAZARDOUS POLYMERIZATION: Will not occur

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicity	CAS#	
Acute Oral Toxicity:		No data available on the product itself
Oral-Components		
4,4'-methylenebis[N-sec-butylaniline]	5285-60-9	LD50 1380 mg/kg Species: Rat
Acute Dermal Toxicity:		No data available on the product itself
Dermal-Components		
4,4'-methylenebis[N-sec-butylaniline]	5285-60-9	LD50 3090 mg/kg Species: Rabbit
Acute Inhalation Toxicity		No data available on the product itself
Inhalation-Components		
Skin Corrosion/ Irritation:		No data available on the product itself
Corrosion/Irritation Components		
Eye Damage/Irritation:		No data available on the product itself
Damage/Irritation Components		
Respiratory Damage/Irritation:		
Damage/irritation Components		
Sensitization:		No data available on the product itself
Sensitizing components		
Germ Cell Mutagenicity		No data available on the product itself
Maternal Toxicity:		No data available on the product itself

Carcinogenicity:

Classification

ACGIH:	Not Classified
IARC:	Quartz(fine fraction) Group 1 Carcinogenic to humans
NTP	Not Listed
OSHA	Not Classified

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY:	CAS#	
Aquatic toxicity:		No data on product itself
Toxicity to Fish-Components		
Toxicity to algae-Components		
Toxicity-Aquatic Invertabrates		
Toxicity to other organisms:		
PERSISTENCE & DEGRADABILITY:		
BIODEGRADABILITY:		No data available on product itself
Biodegradability-Components		
BIOACCUMULATIVE POTENTIAL:		No data available on product itself
BioAccumulaive-Components:		
MOBILITY IN SOIL:		NDA
OTHER ADVERSE EFFECTS:		NDA
AQUATIC RELEASE:		Advise authorities if product has entered or may enter watercourses or sewer drains

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Do not allow this material to drain into sewers / waterways, ditches, containment pools or water supplies. Dispose of contents / containers in accordance with local/regional/international regulations.

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION

PROPER SHIPPING NAME: Not Regulated
HAZARD CLASS:
ID NUMBER:
PACKING GROUP: Not Regulated
LABEL STATEMENT:

HAZARD CLASS: NONE ID NUMBER: NONE D.O.T SHIPPING LABEL: NOT REGULATED BY D.O.T

WATER TRANSPORTATION

PROPER SHIPPING NAME: Not Regulated
HAZARD CLASS:
ID NUMBER:
PACKING GROUP:
LABEL STATEMENT:

AIR TRANSPORTATION

PROPER SHIPPING NAME: Not Regulated
HAZARD CLASS:
ID NUMBER:
PACKING GROUP:
LABEL STATEMENT:

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA (TOXIC SUBSTANCE CONTROL ACT):

CERCLA (COMPREHENSIVE RESPONSE
COMPENSATION, AND LIABILITY ACT): NA

OSHA: 29 CFR 1910.1200 (Hazard Communication required)

WHMIS: NA

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT):

302/304 NA

311/312 HAZARD CATEGORIES: Acute Health Hazard: Yes
Chronic Health Hazard: Yes
Fire Hazard: No
Pressure Release Hazard: No
Reactivity Hazard: No

313 REPORTABLE INGREDIENTS: None

STATE REGULATIONS:

CALIFORNIA PROPOSITION 65 (THE SAFE DRINKING WATER AND TOXICS ENFORCEMENT ACT of 1986)

This product does not contain known levels of any chemicals known to cause cancer or reproductive harm.

SECTION 16: OTHER INFORMATION

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM	
HMIS HAZARD RATING	
HEALTH	2
FLAMMABILITY	1
REACTIVITY	1
PERSONAL PROTECTION	C
4 – Severe, 3 – Serious, 2 – Moderate, 1 - Slight	
C – (Safety glasses, gloves, apron)	

The information provided herein was believed by ChemCo Systems to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of product and to determine the suitability of the product for its intended use.